

Key Features

- ✓ Forged uPVC body for durability and medium pressure applications
- ✓ Valve body Material: uPVC
- ✓ Two ways, normally closed
- ✓ Working Pressure 0.1/0.3 ~ 6 Bar
- ✓ Rated protection: IP65 watertight electrical enclosure
- ✓ Closing feature minimizes water-hammer on shut-off
- ✓ Working Voltage: AC230V, AC240V (50Hz/60Hz), DC24V, AC24V



Model	Size	(mm)	Pressure AC / DC	Length (L) mm	Width (W) mm	Height (H) mm	Weight (Kg)
DHF21CL-15	1/2"	15	0.1 ~ 6 Bar	74	63	138	1.1
DHF21CL-20	3/4"	20	0.1 ~ 6 Bar	78	63	138	1.1
DHF21CL-25	1"	25	0.1 ~ 6 Bar	98	73	148	1.2
DHF21CL-32	1 1/4"	32	0.3 ~ 6 Bar	120	94	171	1.5
DHF21CL-40	1 1/2"	40	0.3 ~ 6 Bar	130	94	180	1.5
DHF21CL-50	2"	50	0.3 ~ 6 Bar	172	155	225	2.6

Optional union connection



Specifications

- Valves body Material : uPVC
- Rated protection : IP65
- Sealing Material : VITON
- Temperature From : -5 to 60°C
- Durability : Corrosive liquid
Acid, Alkali, Air
- Working Pressure : 0.1/0.3 ~ 6 Bar