



CHEMTROL® PC110c Programmable Controller

Designed for pool and spa applications


The PC110c programmable controller, designed for Australian conditions, is equipped with 6 relay output channels for controlling pH and sanitizer. It offers a choice of Free or Total Chlorine (PPM) sensor, ORP for sanitizer reference, oxidizer control backup, TDS, and temperature measurements.

The PC110c programmable controller offers several standard functions in addition to water chemistry control. These include programmable super chlorination, water meter input, 2 programmable relay channels for customizing additional equipment, monitoring chemical tank levels, and the Langelier Saturation Index (LSI) for water balance.

The large, user-friendly 8-line LCD display enables easy monitoring of all process functions at a glance, allowing prompt responses to any changes in conditions.



Mirror the controller screen on your device



Use our app to operate the controller
Anytime, Anywhere

Simple, Reliable and Flexible

Whether it's a swimming pool, spa, aquatic center, water park, or industrial water treatment facility, chemical automation is the easiest and most efficient way to ensure proper water quality. Thanks to the advanced microprocessor technology of the Chemtrol® PC series, you have access to a new standard of sophistication in automated control of sanitizers, oxidizers, and pH. The Chemtrol® PC controller has also been designed to be user-friendly, reliable, and easy to install. Additionally, it comes with an industry-leading five-year electronics warranty.

Standard Features


- ✓ pH control with a choice of acid, co2 or base feed
- ✓ Free available chlorine to control sanitiser level in ppm or mg/ per litre
- ✓ ORP monitoring for sanitizer reference and oxidizer control backup
- ✓ Dissolved solids (TDS) concentration control
- ✓ 2 programmable relay channels for customizing additional equipment
- ✓ Remote alarm
- ✓ Programmable super chlorination
- ✓ Chemical tank levels monitoring
- ✓ Langelier Saturation Index for water balance

CHEMTROL® PC110c Programmable Controller

Hassle free installation

In our commitment to simplify the installation process of CHEMTROL® controllers, we have streamlined everything onto a customized assembly manifold, prepared for easy connection.

- ✓ CHEMTROL® Flow Cell Assembly (FCA)
- ✓ Safety Flow Switch
- ✓ A clear acrylic flow cell designed to regulate water flow for chlorine ppm sensor, equipped with flow adjustment valves and an indicator
- ✓ Sensors holder fittings and water sampling valve
- ✓ Slotted cable ducting for a clean and neat installation



Control your facility 24/7 from anywhere

Smart web-server technology offers true duplex operation, providing identical screens on both the controller and your PC/laptop or any mobile device. This feature is particularly useful for remote monitoring, operator training, troubleshooting, and real-time control of all operating functions. It includes status reports, trend graphs, and automatic alerts via email or text messages.

The CHEMTROL® advantage

Discover the convenience of our waterproof cabinet, seamlessly consolidating all your communication needs

- Remote monitoring and control with a cloud-based web server via Ethernet port or WiFi interface.
- True duplex operation technology mirrors the controller display on your PC or any mobile device.
- Wireless control using a 4G or 5G router. 4-20mA signal for monitoring display outputs.
- Building Management System (BMS) and SCADA Communications protocols include: Modbus IP, Modbus RTU, BACnet IP, BACnet MSTP, and LonWorks.



Automated water treatment since 1976

QUALITY

Proven reliability and performance with 5-year electronics warranty

TECHNOLOGY

Remote monitoring and control with true duplex operation

EXPERIENCE

45+ years of research and development behind our product range

SUSTAINABILITY

Chemical & Energy saving programs designed to reduce operating cost

PEACE OF MIND

Consistent disinfection under varying conditions and regulations

