ARCA 806030W

Sample image

Order symbol : ARCA 806030W

Product nr : 8120139

Description : Cabinet, PC

Remarks : Grey cover with window, 2-point locking, hinges on the long side

EAN : 6418074080103

El. number :

- Finland : 3423215
- Denmark : 8212091951
- Sweden : 2500156

Including : Cabinet base. door with PUR gasket. mounting plate. screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.



Dimensions :	Height	Width	Depth
mm :	800	600	300
inch :	31.5	23.62	11.81

Materials :

Material :	Polycarbonate
Base colour :	RAL_7035
Cover colour :	Clear transparent
Gasket material :	Polyurethane

Temperatures :

Temperature °C (continuous) :	-40 … 80
Temperature °F (continuous) :	-40 … 175

Accessories :

RCS ARCA 8060	Rain canopy set for size 8060 (50 x 600 x 20)
PMK ARCA 60	PoleMounting kit, for pole ⌀100-300mm (585 x 385 x 35)
IDS ARCA 8060	Inner door set (785 x 585 x 35)
DSP ARCA RM	Door stopper ARCA, right, midsize 5070-8060 (22 x 200 x 16)
DRS ARCA 806030	DIN rail frame set (785 x 585 x 35)
MPS ARCA 8060	Mounting plate (730x530x2 mm) (730 x 530 x 2)
DSP ARCA LM	Door stopper ARCA, left, midsize 5070-8060 (22 x 200 x 16)
MPMP ARCA 8060	Mounting plate multiperforated (730x530x2 mm - ⌀3.6 mm) (730 x 530 x 2)
MPP ARCA 8060	Mounting plate perforated (730x530x2 mm - 26x11 mm) (730 x 530 x 2)
MPX ARCA 8060	Mounting plate (730x530 mm) (730 x 530 x 5)

Ratings :

Ingress protection (EN 60529):	IP65;
Impact Resistance (EN 62262):	IK08;
electrical_insulation :	Totally insulated
Halogen free (DIN/VDE 0472, Part 815) :	Yes
UV resistance :	UL 746C
Flammability Rating :	UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C :	960C

Certificates :

Certificate FI 40467

© Fibox Oy, Data subject to change without notice (printed: 05.03.2026)